



- Ⓐ Power inlet (φ60) Terminal M8
- Ⓑ Rubber pads (optional)
- Ⓒ Power inlet (φ60). Breaker capacity (factory), 200V Class:125A (150A:D300B only)/400V Class:75A
- Ⓓ Water for hopper throat IN:Rc3/8 with Y-type strainer (Nomal water volume:5 to 10 l/min.)
- Ⓔ Water for hopper throat OUT:Rc3/8
- ※ Overall machine height increases by approx.47mm with optional rubber pads attached.

Injection unit (screw diameter)	L	L <sub>1</sub>	L <sub>2</sub>	L <sub>3</sub>	L <sub>4</sub>	W <sub>1</sub>	W <sub>2</sub>	W <sub>3</sub>	【H <sub>1</sub> 】	【H <sub>2</sub> 】	【H <sub>3</sub> 】	【H <sub>4</sub> 】
2.5H·2.5U	φ24	4524	833	558	1096	-321	855	370	485	401	481	1691
	φ28	4524	929	654	1096	-225	855	370	485	401	501	1711
	φ32	4524	1006	731	1096	-148	855	370	485	505	625	1835
3.5S·3.5H	φ28	4669	930	655	1470	150	1107	475	632	401	501	1711
	φ32	4774	1006	731	1494	250	1107	475	632	505	625	1835
7H	φ36	4857	1089	814	1494	333	1107	475	632	505	625	1835
	φ40	4975	1187	912	1514	451	1107	475	632	505	630	1840
7H	φ46	5148	1324	1049	1550	624	1107	475	632	570	695	1905

Figures in 【 】 show dimensions with options.

130MEt III (CE)  
OUTSIDE VIEW